



item number	max. number of conductors	max. diameter of conductors (mm ²)	max. load-current capacity (A)	max. voltages (V)	dimension (mm)	weight g / 1 pc	package	color
TYP210_FA	12	2,5	24	400	13,5 x 16 x 95	24	100 pcs in a carton	black
TYP210_HA	12	2,5	24	400	13,5 x 16 x 95	24	100 pcs in a carton	white
TYP310_FA	12	4	32	400	17 x 18 x 106	32	100 pcs in a carton	black
TYP310_HA	12	4	32	400	17 x 18 x 106	32	100 pcs in a carton	white
TYP412_FA	12	6	41	400	17,5 x 19 x 118	37	100 pcs in a carton	black
TYP412_HA	12	6	41	400	17,5 x 19 x 118	37	100 pcs in a carton	white
TYP512_FA	12	10	57	400	21 x 21 x 142	65	100 pcs in a carton	black
TYP512_HA	12	10	57	400	21 x 21 x 142	65	100 pcs in a carton	white
TYP612_FA	12	16	76	400	22 x 22 x 153	80	50 pcs in a carton	black
TYP612_HA	12	16	76	400	22 x 22 x 153	80	50 pcs in a carton	white

material: PA6 (halogen-free)

color: black / white

self-snuffing: yes, within 30 s

temperature resistance: -25 - +85 °C

flaming loop test: 850 °C

meets the requirements: EN 60998-2-1

storage: ČSN 64 0090