



**product description:**

- designed for distribution system with voltage 400 V and with maximum current 16 A
- easy installation of devices with big depth
- possibility to join into and continuous series with and spacing of 71 mm
- boxes can be joined with boxes KP 68/D
- possibility to easily clamp under the device using screwless terminals
- allows to install double-socket
- flexible inlets holes
- labeled insputs for sealing cables and pipes in the flexible material (7x Ø6-12mm; 2x Ø6-16(20)mm; 1x Ø10-20(25)mm; 3x Ø10-25mm)
- installation of cables and pipes is done by removing the flexible membrane inlets and inserting cables or pipes afterwards
- air-tightness even with inserted cable or pipe
- suitable for low energy and passive houses
- prevents airflow through the installation

material: PVC

color: gray, white

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-F

weight: 45 g

meets the requirements: EN 60 670-1

storage: ČSN 64 0090

KPR 68/D\_KA - 66 pcs in carton separately

**accessories:**

- cover V 68
- blind cover ZV 68
- extending frames NR 5X5, NR 68/6, NR 68/10
- screwless terminal plates TYP015, TYP016, TYP017, TYP018

**auxiliary tools:**

non-hammered masonry cutter FR 68 SDS