



item number	for width of cable tray / ladder (A) (mm)	height H (mm)	thickness of metal sheet (mm)	weight (kg/m)	
<b>V 40_S</b>	40	10	0,55	0,26	
<b>V 40_F</b>			0,80	0,46	
<b>V 50_S</b>	50	11	0,55	0,31	🔥
<b>V 50_F</b>			0,80	0,54	🔥
<b>V 50_ZM</b>			0,75	0,42	🔥
<b>V 62_S</b>	62	11	0,55	0,36	🔥
<b>V 62_F</b>			0,80	0,62	🔥
<b>V 75_S</b>	75	11	0,55	0,43	🔥
<b>V 75_F</b>			0,80	0,72	🔥
<b>V 100_S</b>	100	11	0,55	0,53	🔥
<b>V 100_F</b>			0,80	0,91	🔥
<b>V 100_ZM</b>			0,75	0,71	🔥
<b>V 125_S</b>	125	11	0,55	0,64	🔥
<b>V 125_F</b>			0,80	1,10	🔥
<b>V 150_S</b>	150	11	0,55	0,75	🔥
<b>V 150_F</b>			0,80	1,30	🔥
<b>V 200_S</b>	200	11	0,55	0,98	🔥
<b>V 200_F</b>			0,80	1,68	🔥
<b>V 200_ZM</b>			0,75	1,31	🔥
<b>V 250_S</b>	250	11	0,55	1,20	🔥
<b>V 250_F</b>			0,80	2,05	🔥
<b>V 300_S</b>	300	11	0,80	2,07	🔥
<b>V 300_F</b>			1,00	2,73	🔥
<b>V 300_ZM</b>			0,75	1,90	🔥
<b>V 400_S</b>	400	14	1,00	3,43	🔥
<b>V 400_F</b>			1,00	3,63	🔥
<b>V 400_ZM</b>			1,00	3,40	🔥
<b>V 500_S</b>	500	14	1,00	4,22	🔥
<b>V 500_F</b>			1,00	4,80	🔥
<b>V 500_ZM</b>			1,00	4,20	🔥
<b>V 600_S</b>	600	14	1,20	6,27	🔥
<b>V 600_F</b>			1,20	6,70	🔥

product description:

The cable tray cover is used to cover cable trays and cable ladders.  
 The standard length of the cable tray cover is 2 m.  
 Mentioned thickness of the metal plate is just orientation.  
 The fixing of the cover to the tray is done using the cover fixture VU (2 pcs per meter), except for V 40.  
 The V 40 cover may be alternatively fixed using a clamping belt.  
 These items can also be ordered in a varnished version.

surface finish:

S - Pre-Galvanized according to EN 10346, EN 10143, zinc-layer 15 - 27 µm  
 F - Hot Dip Galvanized according to EN ISO 1461, zinc-layer 45 µm (min. 35 µm)  
 ZM - galvanized steel with admixture of magnesium and aluminum according to EN 10346, EN 10143, protective layer 18-31 µm

sales amount:

2 m

meets the requirements: ČSN EN 61537:02

classification:

ČSN 73 0895 P 90-R  
 DIN 4102-12 E 90  
 STN 92 0205 PS 90  
 Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire  
 🔥 products approved for standard constructions  
 🔥 products approved for non-standard constructions

storage:

ČSN EN 60721-3-1