

nominal thread type number bolt lenght diameter NIXSM 6X10\_IX M6 10

This bolt is used to connect cable trays or cable trays with accessories, or to product description:

attach trays to supporting structures.

To protect the cables, the bolt head is inside the cable tray.

Fastening with an bolt provides a conductive bond.

surface finish: IX - stainless steel AISI 316

sales amount: á 100 pc

klasifikace n: ČSN 73 0895 P 90-R

DIN 4102-12 E 90 STN 92 0205 PS 90

Fire classification depends on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire

storage: ČSN EN 60721-3-1



## Risk of injury from cuttingm

Although the cable trays are produced with maximum effort to minimize sharper edges, it is necessary to wear protective gloves to carry, grip and work with cable elements.

## **Material Compatibility**

Ensure that the bolt and nut are compatible with the materials they are fastened to, in order to prevent galvanic corrosion or other undesirable reactions.

## **Regular Inspection**

In environments with high vibrations or temperature fluctuations, it is recommended to regularly inspect the condition of the joints and retighten them if necessary.

## Safe Use

Under normal and foreseeable conditions of use, there are no risks to consumers, provided that proper installation and usage are carried out in accordance with the installation manual.

recycling codes:





